

HULL

- White NPG/ISO gelcoated hull, hand laminated with alternating layers of strand mat and uni-directional 'E' glass locally reinforced
- Partially balsa cored for stiffness
- Gelcoat backup layer is laminated using a 4mm barrier coat of vinyl ester anti-corrosive resin for blister resistance
- Backed by a 5 year blister guarantee
- Built to ABS Plan Certification

DECK

- White, off-white or sand gelcoat with patterned, contrasting non-skid
- Balsa cored uni-directional 'E' glass laminate
- Hand laid with polyester resin

KEEL/BALLAST

- 6,500 lb. high lift fin
- Attached to hull with stainless steel bolts

RUDDER

- Elliptical foam cored rudder blade with uni-directional FRP skins
- 3-1/2" oversized 304 stainless steel rudder post
- Pedestal console steering with 40" s.s. destroyer wheel
- Emergency tiller supplied

INTERIOR

- Structural fiberglass timbers bonded to hull
- Structural bulkheads glass taped to hull and deck
- Bulkheads and risers are pressure laminate or teak faced plywood
- Cabinetry and trim of hand rubbed teak
- Cabin sole is varnished teak and holly
- Overhead liner is teak battened FRP with strategically placed access panels
- A selection of designer fabrics is available for interior upholstery

VENTILATION

- Foreward stateroom: (1) 19" x 19" Lewmar deck hatch; (2) 4" Chrome dorades with guards; (2) 5"x15" portlights
- Aft stateroom: 7" x 12" Lewmar deck hatch; (2) 5" x 15" portlights
- Head: 5"x15" portlights; 7" x 12" Lewmar deck hatch
- Main Cabin: (6) 5"x15" portlights; (1) 16"x16" Lewmar deck hatch; (2) 4" chrome dorade with guards; (1) companionway hatch

ENGINE/ELECTRICAL

- 37 Hp diesel with console mount controls and instrument panel
- 38 gallon fuel capacity (approx.) with remote gauge
- Racor fuel filter
- 16" Fixed propeller on stainless steel shaft
- Brass interior cabin dome lights and berth directional lights
- Courtesy cabin sole night lights
- Navigation lights
- Electric sump pump
- Electric bilge pump
- 12 Volt DC metered panel
- 110 Volt AC shorepower with distribution panel
- 50 ft. shorepower cord
- 40 amp battery charger
- (2) 105 amp battery with selector switch
- UL approved stranded, tinned copper ABYC color coded wiring throughout

GALLEY/PLUMBING

- 3 burner Force 10 propane gimballed stove with oven
- Double stainless steel galley sinks - 9" deep
- Molded top and front load icebox, 4" foam insulated (refrig. optional)
- Built in trash bin
- Hot and cold pressure water and manual fresh water pump
- Extensive lockers, shelves and drawers with teak louvered doors and teak hardwood
- 80 gallon (approx.) freshwater aluminum tanks with visual and remote gauges
- Corian counter tops

HEAD

- (1) Marine head with 'Y' valve and 24 gallon holding tank with deck pumpout and macerator pump
- (1) Separate shower with plexiglass divider in head with drain to sump



